

TC75 Series Rugged Touch Computer

YOUR FRONT LINE TO A SMARTER ENTERPRISE

Your field workforce needs a mobile computer to access the people and information required to maximize efficiency and better serve your customers. You want to give them an enterprise-class handheld built for life out in the field — yet your workers expect a device that is every bit as refined and easy-to-use as their own consumer smartphone. The TC75 Series is the Android™ enterprise touch computer that delivers it all. A choice of Android OS, fortified for use in the enterprise. A rugged design that delivers reliable everyday operation. Anywhere anytime access to virtually any information in your back-end systems. The ability to capture more types of data faster than ever before. Instant push-to-talk communications with co-workers out in the field as well as supervisors, dispatch and more back in the office. 4G LTE support for a robust wireless connection on the world's fastest cellular networks. And a full complement of accessories meets the unique needs of virtually any mobile worker. The TC75 Series — the easy way to empower your field teams with a true mobile office.



Robust Enterprise OS

Mx - Making Android a More

Every TC75 Series ships with Mobility Extensions (Mx), a series of features that make Android a more robust enterpriseclass operating system. Mx minimizes IT support time and maximizes worker productivity and device uptime by providing better control of your mobile devices, application access and Wi-Fi performance and security. Standard Configuration TC75 and TC75x devices come with Google Mobile Services (GMS) which provides integrated Google applications such as Gmail and Google Maps. Professional Configuration TC75 and TC75x devices ship without GMS, removing GMS applications and services. Both configurations are based on Android Open Source (AOSP) and ship with respective Android Enterprise functionality.

World-class Data Capture

An integrated enterprise-class imager offers Zebra's proprietary PRZM Intelligent Imaging technology, a megapixel sensor and advanced optics, enabling the lightning-fast capture of 1D and 2D barcodes in virtually any condition. The rear-facing color camera enables the easy capture of highresolution photos, signatures, videos and more, so workers can capture more types of business intelligence to streamline more business processes.

The front camera allows workers to place a video call to get the on-the-spot assistance they need. And Near Field Communications automates identity verification at facility entry points.

Maximum Data Entry Flexibility with an **Industry Leading Dual Mode Touch Panel**

Let your users choose their preferred data input pair: finger and gloved finger or finger and stylus — ideal for crisp signature capture. The intelligent 4.7 in. display automatically adjusts as needed, unlike competitive devices that require setting adjustments every time the user switches data input method.

Automatically Capture Data and Process Entire Documents

With SimulScan Document Capture, your workers can simultaneously capture barcodes, text fields, phone numbers, images, signatures and even check boxes in the time it takes to press a button, improving invoicing speed, order speed and more.

Superior Audio Quality and Functionality for a New Level of Voice Flexibility

Up to four times the loudness of popular smartphones and noise cancelling technology provides crystal clear audio on both ends of every call. Support for Workforce Connect Push-to-Talk (PTT) Express and Pro provides an instant connection to co-workers in the field, plus supervisors and other support staff back in the office.

Mobility DNA

Every strand of your mobility platform is simpler with Zebra's Mobility DNA. That's because, from the start, you have the industry's

most comprehensive suite of mobility must-haves to accelerate your solution. More off-the shelf end-user apps, more robust administration utilities and easier app development. Purpose built for the enterprise, Mobility DNA makes ease, confidence and value intrinsic to your investment and our full line of Android mobile computers.

PowerPrecision+ Battery for Best-In-ClassPower and Manageability¹

Your workers depend on their mobile devices nearly every minute of the workday. This user replaceable battery ensures that workers have plenty of power for the longest shift and devices are always available. A wealth of easily accessible battery metrics make it easier than ever to identify, remove and replace aging batteries. And with Warm Swap mode, it lets users change the battery without having to power down the device or close open apps

A Robust Accessory Family for Easy On-the-Go Device Management

Accessories include a flexible vehicle cradle for charging — even with snap-on accessories attached. A magnetic stripe reader enables mobile payment. The field attachable trigger handle brings comfort to scan intensive tasks. Select Zebra Bluetooth printers enable anywhere anytime printing. And backroom management is easier and more cost effective than ever thanks to our unique ShareCradle System that accommodates the TC75 Series and future Zebra devices.

Rugged and Ready for All-day Every Day Use Out in the Field

The TC75 Series delivers reliable operation, even after multiple 8 ft./2.4 m drops to concrete and 2,000 consecutive 3.2 ft./1 m tumbles in our punishing tumble test. With IP65 and IP67 sealing, the TC75 Series is dust-tight and can survive complete immersion in water. And the Corning Gorilla Glass touch panel and scanner exit window bring a new level of durability to two of the most vulnerable components on any handheld device.

For more information, visit www.zebra.com/tc75series or access our global contact directory at www.zebra.com/contact

THE TC75 SERIES — THE RIGHT DEVICE MAKES ALL THE DIFFERENCE.

Boost efficiency and customer service with the TC75 Series in:

T&L

- Proof of delivery
- Asset management
- Asset tracking
- Scheduling
- Routing
- · Location services

Field Service

- · Asset management
- Parts inventory
- Invoicing
- Task management
- Location based services
- Technical assistance
- Appointment scheduling
- Service automation

Direct Store Distribution (DSD)/ Route Accounting

- Order automation
- Delivery trackingInventory
- management
- Store setup
- Customer support

Government and Public Safety

- Alternate to two-way radio
- Data collection
- Records query
- Real time data and voice
- ID validation/ ticketing
- Location services
- deployment

 Document on

· Resource

 Document on the scene video and photos

TC75 Series Specifications

Meight 13.3 oz./376 g 4.7 in. High Definition (1280 x 720); exceptionally bright, outdoor viewable; optically bonded to touch panel 1.5 in. High Definition (1280 x 720); exceptionally bright, outdoor viewable; optically bonded to touch panel 1.5 in. High Definition (1280 x 720); exceptionally bright, outdoor viewable; optically bonded to touch panel 1.5 in. High Definition (1280 x 720); exceptionally bright, outdoor viewable; optically bonded to touch panel 1.5 in. High Definition (1280 x 720); exceptionally bright, outdoor viewable; optically bonded to touch panel 1.5 in. High Definition (1280 x 720); exceptionally bright of the panel view provided to touch panel 1.5 in. High Definition (1280 x 720); exceptionally bright of the panel viewable; optically bonded to touch panel 1.5 in. High Definition (1280 x 720); exceptionally bright of the panel viewable; optically bonded to touch panel viewable; optically bright of the panel viewa	PHYSICAL CHARA Dimensions	6.3 in. L x 3.3 in. W x 1.1 in. D/
A.7 in. High Definition (1280 x 720); exceptionally bright, outdoor viewable; optically bonded to touch panel	Differisions	
Imager Window Corning Gorilla Glass Touchpanel Dual mode capacitive touch with stylus or bare or gloved fingertip input (conductive stylus sold separately); Corning Gorilla Glass Backlight LED backlight Power PowerPrecision/ PowerPrecision*: Improved battery technology for advanced state of health and real-time visibility into battery metrics for better battery management Li-lon 3.7 V, 4620 mAh typical; battery swap function Expansion Slot TC75: User accessible MicroSD up to 32GB SDHC and up to 64 GB SDXC TC75s:: User accessible MicroSD up to 32GB SDHC and up to 128 GB SDXC SIM TC75: 2 Nano SIM slot (4FF); 1 Mini SIM/SAM slot (2FF) TC75s:: 2 Nano SIM slot (4FF); 1 Mini SIM/SAM slot (2FF) TC75s:: 2 Nano SIM slot (4FF); 1 Mini SIM/SAM slot (2FF) TC75s:: 2 Nano SIM slot (4FF); 1 Mini SIM/SAM slot (2FF) TC75s:: 2 Nano SIM slot (4FF); 1 Mini SIM/SAM slot (2FF) TC75s:: 2 Nano SIM slot (4FF); 1 Mini SIM/SAM slot (2FF) TC75s:: 2 Nano SIM slot (4FF); 1 Mini SIM/SAM slot (2FF) TC75s:: 2 Nano SIM slot (4FF); 1 Mini SIM/SAM slot (2FF) TC75s:: 2 Nano SIM slot (4FF); 1 Mini SIM/SAM slot (2FF) TC75s:: 1 Nano SIM slot (4FF); 1 Mini SIM/SAM slot (2FF) TC75s:: 1 Nano SIM slot (4FF); 1 Mini SIM/SAM slot (2FF) TC75s:: 2 Nano SIM slot (4FF); 1 Mini SIM/SAM slot (2FF) TC75s:: 2 Nano SIM slot (4FF); 1 Mini SIM/SAM slot (2FF) TC75s:: 2 Nano SIM slot (4FF); 1 Mini SIM/SAM slot (2FF) TC75s:: 1 Nano SIM slot (4FF); 1 Mini SIM/SAM slot (2FF) TC75s:: 1 Nano SIM slot (4FF); 1 Mini SIM/SAM slot (2FF) TC75s:: 1 Nano SIM slot (4FF); 1 Mini SIM/SAM slot (2FF) TC75s:: 1 Nano SIM slot (4FF); 1 Mini SIM/SAM slot (2FF) TC75s:: 1 Nano SIM slot (4FF); 1 Mini SIM/SAM slot (2FF) TC75s:: 1 Nano SIM slot (4FF); 1 Mini SIM/SAM slot (2FF) TC75s:: 1 Nano SIM slot (4FF); 1 Mini SIM/SAM slot (2FF) TC75s:: 1 Nano SIM slot (4FF); 1 Mini SIM/SAM slot (2FF) TC75s:: 1 Nano SIM slot (4FF); 1 Mini SIM/SAM slot (2FF) TC75s:: 1 Nano SIM slot (4FF); 1 Mini SIM/SAM slot (2FF) TC75s:: 1 Nano SIM slot (4FF); 1 Mini SIM/SAM slot (2FF) TC75s:: 1 Nano SIM slot (4FF); 1 Min	Weight	13.3 oz./376 g
Touchpanel Dual mode capacitive touch with stylus or bare or gloved fingertip input (conductive stylus sold separately); Corning Gorilla Glass Backlight LED backlight Power PowerPrecision/ PowerPrecision+1: Improved battery technology for advanced state of health and real-time visibility into battery metrics for better battery management Li-lon 3.7 V, 4620 mAh typical; battery swap function Expansion Slot TC75: User accessible MicroSD up to 32GB SDHC and up to 64 GB SDXC TC75x: User accessible MicroSD up to 32GB SDHC and up to 128 GB SDXC SIM TC75: 2 Nano SIM slot (4FF); 1 Mini SIM/SAM slot (2FF) TC75x: 2 Nano SIM slot (4FF); 1 Mini SIM/SAM slot (2FF) TC75x: 2 Nano SIM slot (4FF); 1 Mini SIM/SAM slot (2FF) TC75x: 2 Nano SIM slot (4FF); 1 Mini SIM/SAM slot (2FF) TC75x: 2 Nano SIM slot (4FF); 1 Mini SIM/SAM slot (2FF) TC75x: 2 Nano SIM slot (4FF); 1 Mini SIM/SAM slot (2FF) TC75x: 2 Nano SIM slot (4FF); 1 Mini SIM/SAM slot (2FF) TC75x: 1 Nano SIM slot (4FF); 1 Mini SIM	Display	bright, outdoor viewable; optically bonded to
or gloved fingertip input (conductive stylus sold separately); Corning Gorilla Glass Backlight LED backlight Power PowerPrecision/PowerPrecision+1: Improved battery technology for advanced state of health and real-time visibility into battery metrics for better battery management Li-lon 3.7 V, 4620 mAh typical; battery swap function Expansion Slot TC75: User accessible MicroSD up to 32GB SDHC and up to 64 GB SDXC TC75x: User accessible MicroSD up to 32GB SDHC and up to 128 GB SDXC SIM TC75: 2 Nano SIM slot (4FF); 1 Mini SIM/SAM slot (2FF) TC75x: 2 Nano SIM slot (4FF); 1 Mini SIM (2FF) TC75x: 2 Nano SIM slot (4FF); 1 Mini SIM (2FF) Network Connections Notification Audible tone; multi-color LEDs; vibration Keypad On-screen keypad; Enterprise Keyboard Voice and Audio Three microphone support with noise cancellation; vibrate alert; speaker; Bluetooth wireless headset support, High quality speaker phone; PTT headset support, High quality speaker phone; PTT headset support; Cellular circuit switch voice; HD Voice PERFORMANCE CHARACTERISTICS CPU TC75: 1.7 GHz dual core processor TC75x: 1.8 GHz hex core 64 bit processor Operating System TC75: 1 GB RAM / 8 GB Flash pSLC TC75x: 2 GB RAM / 16 GB Flash pSLC or 4 GB RAM / 32 GB Flash pSLC USER ENVIRONMENT Operating Temp. -4° F to 152° F/-20° C to 50° C Storage Temp. -40° F to 158° F/-40° C to 70° C Humidity S% to 85% non-condensing Multiple 8 ft./2.4 m drop to concrete at room temperature per MIL-STD 810G, Multiple 6 ft./1.8 m drop to concrete across full operating temperature range Tumble Specification Z,000 3.2 ft./1.0 m tumbles; meets and exceeds IEC	Imager Window	Corning Gorilla Glass
Power PowerPrecision/PowerPrecision+*: Improved battery technology for advanced state of health and real-time visibility into battery metrics for better battery management Li-lon 3.7 V, 4620 mAh typical; battery swap function TC75: User accessible MicroSD up to 32GB SDHC and up to 64 GB SDXC TC75x: User accessible MicroSD up to 32GB SDHC and up to 128 GB SDXC SIM TC75: 2 Nano SIM slot (4FF); 1 Mini SIM/SAM slot (2FF) TC75x: 2 Nano SiM slot (4FF); 1 Mini SiM/Sam slot (2FF)	Touchpanel	or gloved fingertip input (conductive stylus sold
battery technology for advanced state of health and real-time visibility into battery metrics for better battery management Li-lon 3.7 V, 4620 mAh typical; battery swap function Expansion Slot TC75: User accessible MicroSD up to 32GB SDHC and up to 64 GB SDXC TC75x: User accessible MicroSD up to 32GB SDHC and up to 128 GB SDXC SIM TC75: 2 Nano SIM slot (4FF); 1 Mini SIM/SAM slot (2FF) TC75x: 2 Nano SIM slot (4FF); 1 Mini SIM/SAM slot (2FF) TC75x: 2 Nano SIM slot (4FF); 1 Mini SIM/SAM slot (2FF) Network Connections Notification Audible tone; multi-color LEDs; vibration Keypad On-screen keypad; Enterprise Keyboard Voice and Audio Three microphone support with noise cancellation; vibrate alert; speaker; Bluetooth wireless headset support, High quality speaker phone; PTT headset support; Cellular circuit switch voice; HD Voice PERFORMANCE CHARACTERISTICS CPU TC75: 1.7 GHz dual core processor TC75x: 1.8 GHz hex core 64 bit processor TC75x: 1.8 GHz hex core 64 bit processor TC75x: Android 5.1 Lollipop with Zebra's Mobility Extensions (Mx) TC75: Android 7.1 (Nougat) with Mx Memory TC75: 1 GB RAM / 8 GB Flash pSLC TC75x: 2 GB RAM / 16 GB Flash pSLC or 4 GB RAM / 32 GB Flash pSLC USER ENVIRONMENT Operating Temp. -4° F to 122° F/-20° C to 50° C Storage Temp. Humidity S% to 85% non-condensing Drop Specification Multiple 8 ft./2.4 m drop to concrete at room temperature per MIL-STD 810G, Multiple 6 ft./1.8 m drop to concrete across full operating temperature range Tumble Specification 2,000 3.2 ft./1.0 m tumbles; meets and exceeds IEC	Backlight	LED backlight
and up to 64 GB SDXC TC75x: User accessible MicroSD up to 32GB SDHC and up to 128 GB SDXC TC75x: User accessible MicroSD up to 32GB SDHC and up to 128 GB SDXC TC75: 2 Nano SIM slot (4FF); 1 Mini SIM/SAM slot (2FF) TC75x: 2 Nano SIM slot (4FF); 1 Mini SIM (2FF) TC75x: 2 Nano SIM slot (4FF); 1 Mini SIM (2FF) Network Connections Notification Audible tone; multi-color LEDs; vibration Keypad On-screen keypad; Enterprise Keyboard Voice and Audio Three microphone support with noise cancellation; vibrate alert; speaker; Bluetooth wireless headset support, High quality speaker phone; PTT headset support; Cellular circuit switch voice; HD Voice PERFORMANCE CHARACTERISTICS CPU TC75: 1.7 GHz dual core processor TC75x: 1.8 GHz hex core 64 bit processor Operating System TC75: Android 5.1 Lollipop with Zebra's Mobility Extensions (Mx) TC75x: Android 7.1 (Nougat) with Mx Memory TC75: 1.6 B RAM / 8 GB Flash pSLC TC75x: 2 GB RAM / 16 GB Flash pSLC or 4 GB RAM / 32 GB Flash pSLC USER ENVIRONMENT Operating Temp. 40° F to 122° F/-20° C to 50° C Humidity 5% to 85% non-condensing Drop Specification Multiple 8 ft./2.4 m drop to concrete at room temperature per MIL-STD 810G, Multiple 6 ft./1.8 m drop to concrete across full operating temperature range Tumble Specification 2,000 3.2 ft./1.0 m tumbles; meets and exceeds IEC	Power	battery technology for advanced state of health and real-time visibility into battery metrics for better battery management Li-lon 3.7 V, 4620 mAh typical;
Network Connections Notification Audible tone; multi-color LEDs; vibration Keypad On-screen keypad; Enterprise Keyboard Voice and Audio Three microphone support with noise cancellation; vibrate alert; speaker; Bluetooth wireless headset support, High quality speaker phone; PTT headset support; Cellular circuit switch voice; HD Voice PERFORMANCE CHARACTERISTICS CPU TC75: 1.7 GHz dual core processor TC75x: 1.8 GHz hex core 64 bit processor TC75: 1.8 GHz hex core 64 bit processor TC75x: Android 5.1 Lollipop with Zebra's Mobility Extensions (Mx) TC75x: 2 GB RAM / 16 GB Flash pSLC TC75x: 2 GB RAM / 16 GB Flash pSLC or 4 GB RAM / 32 GB Flash pSLC USER ENVIRONMENT Operating Temp. -4° F to 122° F/-20° C to 50°C Storage Temp. Humidity S% to 85% non-condensing Multiple 8 ft./2.4 m drop to concrete at room temperature per MIL-STD 810G, Multiple 6 ft./1.8 m drop to concrete across full operating temperature range Tumble Specification 2,000 3.2 ft./1.0 m tumbles; meets and exceeds IEC	Expansion Slot	and up to 64 GB SDXC TC75x: User accessible MicroSD up to 32GB SDHC
Connections Audible tone; multi-color LEDs; vibration Keypad On-screen keypad; Enterprise Keyboard Voice and Audio Three microphone support with noise cancellation; vibrate alert; speaker; Bluetooth wireless headset support, High quality speaker phone; PTT headset support; Cellular circuit switch voice; HD Voice PERFORMANCE CHARACTERISTICS CPU TC75: 1.7 GHz dual core processor TC75x: 1.8 GHz hex core 64 bit processor Operating System TC75: Android 5.1 Lollipop with Zebra's Mobility Extensions (Mx) TC75x: Android 7.1 (Nougat) with Mx Memory TC75: 1 GB RAM / 8 GB Flash pSLC TC75x: 2 GB RAM / 16 GB Flash pSLC or 4 GB RAM / 32 GB Flash pSLC USER ENVIRONMENT Operating Temp. Operating Temp. -4° F to 122° F/-20° C to 50° C Storage Temp. -40° F to 158° F/-40° C to 70° C Humidity 5% to 85% non-condensing Drop Specification Multiple 8 ft./2.4 m drop to concrete at room temperature per MIL-STD 810G, Multiple 6 ft./1.8 m drop to concrete across full operating temperature range Tumble Specification 2,000 3.2 ft./1.0 m tumbles; meets and exceeds IEC	SIM	
Voice and Audio Three microphone support with noise cancellation; vibrate alert; speaker; Bluetooth wireless headset support, High quality speaker phone; PTT headset support; Cellular circuit switch voice; HD Voice PERFORMANCE CHARACTERISTICS CPU TC75: 1.7 GHz dual core processor TC75x: 1.8 GHz hex core 64 bit processor TC75x: 1.8 GHz hex core 64 bit processor Mobility Extensions (Mx) TC75: 1 GB RAM / 8 GB Flash pSLC TC75x: 2 GB RAM / 16 GB Flash pSLC or 4 GB RAM / 32 GB Flash pSLC USER ENVIRONMENT Operating Temp. 4° F to 122° F/-20° C to 50° C Humidity 5% to 85% non-condensing Drop Specification Multiple 8 ft./2.4 m drop to concrete at room temperature per MIL-STD 810G, Multiple 6 ft./1.8 m drop to concrete across full operating temperature range Tumble Specification 2,000 3.2 ft./1.0 m tumbles; meets and exceeds IEC		USB 2.0 High Speed (host and client); WLAN
Voice and Audio Three microphone support with noise cancellation; vibrate alert; speaker; Bluetooth wireless headset support, High quality speaker phone; PTT headset support; Cellular circuit switch voice; HD Voice PERFORMANCE CHARACTERISTICS CPU TC75: 1.7 GHz dual core processor TC75x: 1.8 GHz hex core 64 bit processor TC75x: 1.8 GHz hex core 64 bit processor TC75x: Android 5.1 Lollipop with Zebra's Mobility Extensions (Mx) TC75x: Android 7.1 (Nougat) with Mx Memory TC75: 1.6 B RAM / 8 GB Flash pSLC TC75x: 2 GB RAM / 16 GB Flash pSLC or 4 GB RAM / 32 GB Flash pSLC USER ENVIRONMENT Operating Temp. -4° F to 122° F/-20° C to 50° C Storage Temp. -40° F to 158° F/-40° C to 70° C Humidity Twice is the storage of the stor	Notification	Audible tone; multi-color LEDs; vibration
vibrate alert; speaker; Bluetooth wireless headset support, High quality speaker phone; PTT headset support; Cellular circuit switch voice; HD Voice PERFORMANCE CHARACTERISTICS CPU TC75: 1.7 GHz dual core processor TC75x: 1.8 GHz hex core 64 bit processor TC75x: 1.8 GHz hex core 64 bit processor TC75x: Android 5.1 Lollipop with Zebra's Mobility Extensions (Mx) TC75x: Android 7.1 (Nougat) with Mx Memory TC75: 1 GB RAM / 8 GB Flash pSLC TC75x: 2 GB RAM / 16 GB Flash pSLC or 4 GB RAM / 32 GB Flash pSLC USER ENVIRONMENT Operating Temp. -4° F to 122° F/-20° C to 50° C Storage Temp. 40° F to 158° F/-40° C to 70° C Humidity Two 85% non-condensing Multiple 8 ft./2.4 m drop to concrete at room temperature per MIL-STD 810G, Multiple 6 ft./1.8 m drop to concrete across full operating temperature range Tumble Specification 2,000 3.2 ft./1.0 m tumbles; meets and exceeds IEC	Keypad	On-screen keypad; Enterprise Keyboard
CPU TC75: 1.7 GHz dual core processor TC75x: 1.8 GHz hex core 64 bit processor TC75x: Android 5.1 Lollipop with Zebra's Mobility Extensions (Mx) TC75x: Android 7.1 (Nougat) with Mx TC75x: 2 GB RAM / 8 GB Flash pSLC TC75x: 2 GB RAM / 16 GB Flash pSLC or 4 GB RAM / 32 GB Flash pSLC USER ENVIRONMENT Operating Temp. -4° F to 152° F/-20° C to 50° C Storage Temp. -40° F to 158° F/-40° C to 70° C Humidity 5% to 85% non-condensing Multiple 8 ft./2.4 m drop to concrete at room temperature per MIL-STD 810G, Multiple 6 ft./1.8 m drop to concrete across full operating temperature range Tumble Specification 2,000 3.2 ft./1.0 m tumbles; meets and exceeds IEC	Voice and Audio	vibrate alert; speaker; Bluetooth wireless headset support, High quality speaker phone; PTT headset
TC75x: 1.8 GHz hex core 64 bit processor Operating System TC75: Android 5.1 Lollipop with Zebra's Mobility Extensions (Mx) TC75x: Android 7.1 (Nougat) with Mx Memory TC75: 1 GB RAM / 8 GB Flash pSLC TC75x: 2 GB RAM / 16 GB Flash pSLC or 4 GB RAM / 32 GB Flash pSLC TC75x: 2 GB RAM / 16 GB Flash pSLC or 4 GB RAM / 32 GB Flash pSLC USER ENVIRONMENT Operating Temp. -4° F to 122° F/-20° C to 50°C Storage Temp. -40° F to 158° F/-40° C to 70° C Humidity 5% to 85% non-condensing Multiple 8 ft./2.4 m drop to concrete at room temperature per MIL-STD 810G, Multiple 6 ft./1.8 m drop to concrete across full operating temperature range Tumble Specification 2,000 3.2 ft./1.0 m tumbles; meets and exceeds IEC	PERFORMANCE (CHARACTERISTICS
Mobility Extensions (Mx) TC75x: Android 7.1 (Nougat) with Mx Memory TC75: 1 GB RAM / 8 GB Flash pSLC TC75x: 2 GB RAM / 16 GB Flash pSLC or 4 GB RAM / 32 GB Flash pSLC USER ENVIRONMENT Operating Temp. -4° F to 122° F/-20° C to 50° C Storage Temp. -40° F to 158° F/-40° C to 70° C Humidity 5% to 85% non-condensing Multiple 8 ft./2.4 m drop to concrete at room temperature per MIL-STD 810G, Multiple 6 ft./1.8 m drop to concrete across full operating temperature range Tumble Specification 2,000 3.2 ft./1.0 m tumbles; meets and exceeds IEC	CPU	
TC75x: 2 GB RAM / 16 GB Flash pSLC or 4 GB RAM / 32 GB Flash pSLC USER ENVIRONMENT Operating Temp4° F to 122° F/-20° C to 50° C Storage Temp40° F to 158° F/-40° C to 70° C Humidity 5% to 85% non-condensing Drop Specification Multiple 8 ft./2.4 m drop to concrete at room temperature per MIL-STD 810G, Multiple 6 ft./1.8 m drop to concrete across full operating temperature range Tumble Specification 2,000 3.2 ft./1.0 m tumbles; meets and exceeds IEC	Operating System	Mobility Extensions (Mx)
Operating Temp. -4° F to 122° F/-20° C to 50° C Storage Temp. -40° F to 158° F/-40° C to 70° C Humidity 5% to 85% non-condensing Multiple 8 ft./2.4 m drop to concrete at room temperature per MIL-STD 810G, Multiple 6 ft./1.8 m drop to concrete across full operating temperature range Tumble Specification 2,000 3.2 ft./1.0 m tumbles; meets and exceeds IEC	Memory	TC75x: 2 GB RAM / 16 GB Flash pSLC or 4 GB RAM /
Storage Temp40° F to 158° F/-40° C to 70° C Humidity 5% to 85% non-condensing Drop Specification Multiple 8 ft./2.4 m drop to concrete at room temperature per MIL-STD 810G, Multiple 6 ft./1.8 m drop to concrete across full operating temperature range Tumble Specification 2,000 3.2 ft./1.0 m tumbles; meets and exceeds IEC	USER ENVIRONM	IENT
Humidity 5% to 85% non-condensing Drop Specification Multiple 8 ft./2.4 m drop to concrete at room temperature per MIL-STD 810G, Multiple 6 ft./1.8 m drop to concrete across full operating temperature range Tumble Specification 2,000 3.2 ft./1.0 m tumbles; meets and exceeds IEC	Operating Temp.	-4° F to 122° F/-20° C to 50°C
Drop Specification Multiple 8 ft./2.4 m drop to concrete at room temperature per MIL-STD 810G, Multiple 6 ft./1.8 m drop to concrete across full operating temperature range Tumble Specification 2,000 3.2 ft./1.0 m tumbles; meets and exceeds IEC	Storage Temp.	-40° F to 158° F/-40° C to 70° C
temperature per MIL-STD 810G, Multiple 6 ft./1.8 m drop to concrete across full operating temperature range Tumble Specification 2,000 3.2 ft./1.0 m tumbles; meets and exceeds IEC	Humidity	5% to 85% non-condensing
	Drop Specification	temperature per MIL-STD 810G, Multiple 6 ft./1.8 m drop to concrete across full operating temperature
	Tumble Specification	

USER ENVIRONMENT (CONTINUED)		
Sealing	IP65 and IP67 per applicable IEC sealing specifications	
Vibration	4 g's PK Sine (5 Hz to 2 kHz); 0.04g2/Hz Random (20 Hz to 2 kHz); 60 minute duration per axis, 3 axis	
Thermal Shock	-40° F to 158° F/-40° C to 70° C rapid transition	
Electrostatic Discharge (ESD)	+/-15kVdc air discharge +/-8kVdc direct discharge +/-8kVdc indirect discharge	
INTERACTIVE SE	NSOR TECHNOLOGY (IST)	
Light Sensor	Automatically adjusts display backlight brightness	
Motion Sensor	eCompass, 3-axis Gyro, 3-axis accelerometer	
DATA CAPTURE		
Scanning	SE4750 imager (1D and 2D); extraordinary range: Scan range — Code 39 barcode: 20 Mil: 1.6 in to 36.3 in/4.1 cm to 92.2cm 3 Mil: 2.8 in to 6.2 in/7.1 cm to 15.9 cm	
Camera	Rear – 8 MP autofocus; f/2.4 aperture (TC75) Rear – 13MP autofocus (TC75x) Front – 1.3 MP fixed focus (TC75/TC75x)	
NFC	TC75: Type A and B, Felica and ISO 15693 cards. P2P mode and Card Emulation via UICC and Host TC75X: ISO 14443 Type A and B; Felica, and ISO 15693 cards. P2P mode and Card Emulation via UICC and Host	
WIRELESS WAN I	DATA AND VOICE COMMUNICATIONS	
Radio Frequency Band	TC75 Worldwide: LTE: 800/850/900/1800/2100/2600 (FDD 20,5,8,3,1,7); UMTS/HSPA/HSPA+: 850/900/1900/2100; GSM/GPRS/ EDGE: 850/900/1800/1900 Americas: LTE: 700/850/1900/AWS/2100 (FDD 17,5,2,4,1); UMTS/ HSPA/HSPA+: 850, 900, AWS, 1900, 2100; GSM/GPRS/ EDGE: 850/900/1800/1900 TC75x Worldwide:	
	Worldwide: LTE: 700,800/850/900/1800/2100/2600 (FDD 28,20,5,8,3,1,7); UMTS/HSPA/HSPA+: 850/900/1900/2100; GSM/GPRS/EDGE: 850/900/1800/1900 Americas: LTE: 700/850/1900/AWS/2100, (FDD 13,12,17,5,26,2,25,4,1); UMTS/HSPA/HSPA+: 850, 900, AWS, 1900, 2100 GSM/GPRS/EDGE: 850/900/1800/1900; CDMA: 850,1900 (BC0, BC10, BC1)	
GPS	TC75: Integrated, Autonomous, Assisted GPS (A-GPS), Navstar, GLONASS TC75x: Integrated, Autonomous, Assisted GPS (A-GPS), Navstar, GLONASS, Beidou	

TC75 Series Specifications (continued)

WIRELESS LAN	
Radio	TC75: IEEE® 802.11a/b/g/n/d/h/i/k/r TC75x: 2x2 MIMO; IEEE 802.11 a/b/g/n/ac/d/h/i/k/r/w
Data Rates	TC75 5GHz: 802.11a/n — up to 150 Mbps; 2.4GHz: 802.11b/g/n — up to 72.2 Mbps TC75x 5GHz: 802.11a/n/ac — up to 866.7 Mbps; 2.4GHz: 802.11b/g/n — up to 144 Mbps
Operating Channels	TC75 Chan 1 - 13 (2412 - 2472 MHz); Chan 36 - 165 (5180 - 5825 MHz) Channel Bandwidth: 20, 40 MHz TC75x Chan 1 - 13 (2412 - 2472 MHz), Chan 36 - 165 (5180 - 5825 MHz), Chan 138, Chan 142 Channel Bandwidth: 20, 40, 80 MHz Actual operating channels/ frequencies depend on regulatory rules and certification agency
Security and Encryption	WEP (40 or 104 bit); WPA/WPA2 Personal (TKIP, and AES); WPA/WPA2 Enterprise (TKIP and AES) — EAP-TTLS (PAP, MSCHAP, MSCHAPV2), EAP-TLS, PEAPV0-MSCHAPv2, PEAPV1-EAP-GTC, EAP Fast² and LEAP Data in Motion: FIPS 140-2 Level 1 Data at Rest: FIPS 140-2 Level 1
Features	TC75: Wi-Fi Multimedia" (WMM), Soft AP, Wi-Fi Direct, Miracast TC75x: Wi-Fi Multimedia (WMM), Soft AP, MIMO with 2 Spatial Streams, 256 QAM Modulation on 56 GHz radio; Maximum Ratio Combining (MRC), Tx/Rx Low-Density Parity Check (LDPC), Transmit Beamforming(TxBF) and Beamformee (BFee) capability, Full IEEE 802.11 a/b/g/n legacy compatibility
Certifications	TC75: WFA (802.11n, WMM-PS, Wi-Fi Direct, WPS, Miracast) TC75x: WFA (802.11n, 802.11ac, Mobile AP, Personal Hotspot, Miracast, WMM-PS, WMM-AC and Voice Enterprise)
Fast Roam	PMKID caching, Cisco CCKM, 802.11r, OKC

WIRELESS PAN	
Bluetooth	Class 2, Bluetooth v4.0 (Bluetooth® Smart technology) BT Wideband support HFPv1.6 Bluetooth v4.1 LE (TC75x only)

COMMUNICATION AND MESSAGING

Workforce Connect PTT Express (included) provides instant push-to-talk (PTT) small group communications across Wi-Fi networks. Workforce Connect PTT Pro (supported) provides a scalable network agnostic push-totalk solution which also includes messaging, location services and two-way radio integration. Workforce Connect Voice client (supported) enables the TC75 Series to function as a full featured mobile telephone with multi-line capability across Wi-Fi networks.

ADDITIONAL MOBILITY DNA SOLUTIONS



Mobility DNA solutions help you get more value out of our mobile computers by adding functionality as well as simplifying deployment and management of our mobile devices. For more information on these Zebra-only features, please visit www.zebra.com/mobilitydna



Enterprise Keyboard



Enterprise Home Screen



Stage Now



AppGallery



EMDK



Enterprise Browser



SimulScan

Available Mobility DNA features may vary by model.

WARRANTY

Subject to the terms of Zebra's hardware warranty statement, the TC75 Series is warranted against defects in workmanship and materials for a period of 1 (one) year from the date of shipment. For complete warranty statement, please visit: http://www.zebra.com/warranty

RECOMMENDED SERVICES

Zebra OneCare; Managed Device Service

- 1. PowerPrecision+ batteries are available only on TC75x models and provide advanced state of health and advanced state of charge metrics.
- 2. EAP Fast supported on TC75 models only.

Specifications subject to change without notice and some features may vary by model.









NA and Corporate Headquarters +1 800 423 0442 inquiry4@zebra.com

Asia-Pacific Headquarters +65 6858 0722 contact.apac@zebra.com

EMEA Headquarters zebra.com/locations contact.emea@zebra.com Latin America Headquarters +18479552283 la.contactme@zebra.com